

COMPLETE INSTRUMENTS & OPTIONS

ITEM	PART#	DESCRIPTION	List Price (USD)
970-C	970C000	Sugar Consistency Monitor - Includes sensor, transmitter (NEMA 1), splash hood, manual, 1-3/4 inch rotor and spare parts kit.	\$3,090.00
NEMA 4X	970C100	NEMA 4X enclosure option for 970-C transmitter	\$425.00
970-M	970M000	Sugar Oversaturation Monitor - Includes sensor, transmitter (NEMA 1) and manual.	\$2,538.00
NEMA 4X	977C100	NEMA 4X enclosure option for 970-M transmitter	\$425.00
971-CM	971C000	Syrup Brix Monitor (Manual Temperature Compensation) - Includes sensor, transmitter (NEMA 1), splash hood, manual, 3 inch rotor and spare parts	\$3,070.00
971-CA	971C100	Syrup Brix Monitor (Automatic Temperature Compensation) - Includes sensor, transmitter (NEMA 1), temperature sensor, splash hood, manual. 3 inch rotor and spare parts kit.	\$3,560.00
NEMA 4X	977C100	NEMA 4X enclosure option for 971-C transmitter	\$425.00
977-C	977C000	Turbidimeter/Low Suspended Solids Monitor - Includes sensor, transmitter (NEMA 1), 25 ft of sensor cable, compression fitting, safety chain and manual.	\$2,680.00
NEMA 4X	977C100	NEMA 4X enclosure option for 977-C transmitter	\$425.00
Pipe Insertion Adapter	977C200	Pipe insertion/removal adapter option for 977-C Insertion Sensor	\$165.00
Dual Alarms	977C300	Dual alarm option for 977-C - Provides 2 adjustable 10 Amp high/low contacts and LED alarm indication on transmitter panel.	\$390.00
Submersible Sensor	977C400	Submersible-type sensor option for 977-C - Includes submersible sensor with 50 feet of cable instead of insertion sensor with 25 feet of cable.	\$200.00
Light Shield	977C500	Light shield option for 977-C Submersible Sensor - To protect sensor from ambient light.	\$300.00
12 VDC Power	977C600	12 VDC powered transmitter option for 977-C - Allows transmitter to operate from 12 VDC power source instead of AC power.	\$250.00
24 VDC Power	977C601	24 VDC powered transmitter option for 977-C - Allows transmitter to operate from 24 VDC power source instead of AC power.	\$250.00
Cable	977C900	Extra interconnecting cable for 977-C (per foot) - Additional cable for connecting sensor to transmitter.	\$1.69
978-C	978C000	Suspended Solids Monitor - (Please specify solids range/type and application: 0-2000ppm, 0-0.2000%, 0-2.000%, 0-20%, 0-200% solids) - Includes sensor, transmitter (NEMA 1), 25 ft of sensor cable, compression fitting, safety chain and manual.	\$2,800.00
NEMA 4X	978C100	NEMA 4X enclosure option for 978-C transmitter	\$425.00
Pipe Insertion Adapter	978C200	Pipe insertion/removal adapter option for 978-C Insertion Sensor	\$165.00
Dual Alarms	978C300	Dual alarm option for 978-C - Provides 2 adjustable 10 Amp high/low contacts and LED alarm indication on transmitter panel.	\$390.00
Submersible Sensor	978C400	Submersible-type sensor option for 978-C - Includes submersible sensor with 50 feet of cable instead of insertion sensor with 25 feet of cable.	\$200.00
Light Shield	978C500	Light shield option for 978-C Submersible Sensor - To protect sensor from ambient light.	\$300.00
12 VDC Power	978C600	12 VDC powered transmitter option for 978-C - Allows transmitter to operate from 12 VDC power source instead of AC power.	\$250.00
24 VDC Power	978C601	24 VDC powered transmitter option for 978-C - Allows transmitter to operate from 24 VDC power source instead of AC power.	\$250.00
Cable	978C900	Extra interconnecting cable for 978-C (per foot) - Additional cable for connecting sensor to transmitter.	\$1.69